

Full HD@25fps Vari-Focal IP IR Dome Camera



Main Features

- ⇒ 1/2.7" Progressive Scan CMOS
- ⇒ Full HD 1080p / HD 720p Real-time at Dual Streaming
- ⇒ H.264 and MJPEG compression
- ⇒ 3-9 mm Varifocal Lens
- ⇒ Built-in IR Illuminator (effective distance: 25m)
- ⇒ WDR, 3D-DNR, ICR, Motion Detection, Privacy Masks
- ⇒ Micro SDHC 32GB support
- ⇒ Two Way Audio
- ⇒ Sun Shield & Cable Management

Feature	Specification
Image Sensor	1/2.7" Progressive Scan CMOS
Minimum Illumination	0.2 lux @ F1.2
Shutter Speed	1~ 1/10000 sec.
White Balance	Manual / AWB / ATW
Lens	F1.2 / f = 3-9 mm
Video Compression	H.264/MJPEG
Video Streaming	H.264 + MJPEG/H.264 + H.264
Resolution	H.264 : Full HD 1080p/SXGA/HD 720p/D1/VGA/CIF/QVGA, MJPEG : Full HD 1080p/SXGA/HD 720p/D1/VGA/CIF/QVGA
Frame Rate	HD 25/30 fps, Full HD 30 fps
Digital Zoom	Support
Motion detection	On/Off
Privacy Mask	Support
Privacy Mask Type	Color
ICR	Auto/On/Off
Tampering Alarm	On/Off
Audio Input	Two Way Audio: Line out, Line in/mic in
Audio Compression	G.711/G.726
Alarm IN	5V 10kI pull up
Alarm Out	Photo Relay Output 300VDC/AC
Event Notification	HTTP, FTP, SMTP
Multiple Languages	English, French, German, Italian, Korean, Simplified Chinese, Russian
Interface	10/100Mbps Ethernet (RJ-45)
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Password Levels	User and Administrator

Feature	Specification
Security	HTTPS, IP Filter, IEEE 802.1X
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari
User Account	20
IR	24Pcs LEDs, Upto 30 Mtrs
Micro SD	micro SDHC 32GB support
Audio Connector	4 pins terminal block
Analog Video	1.0 Vp-p / 75 I, BNC
Operating Temperature	-10° ~ 50°C (14° ~ 122° F)
Humidity	10% to 90%, No Condensation
Power Source	DC12V/AC24V/PoE
Power Consumption	System: 5W (Built-in IR Illuminator: +3W, Motorized Lens: +3.6W)
Regulatory	CE, FCC, RoHS Compliant
Dimension	Ø 149 x 131 mm (Ø 5.9 x 5.2 inches)
Weight	700gm (1.5lbs)