

## 2Mp Full HD Vandal-proof IP Dome Camera



### Main Features

- ⇒ 1/3" 2.0 Megapixel Progressive Scan CMOS Image Sensor
- ⇒ High-Performance DSP
- ⇒ H.264 Video Compression and JPEG Image Capture
- ⇒ Max 25fps@1080P Resolution
- ⇒ 3.6mm Lens
- ⇒ Supports PoE and IP66 Rating Vandal Proof
- ⇒ Max 32GB Micro SD Card for Local Storage
- ⇒ Built-in Web server, CMOB & KVMS(CMS)

Feature	Specification
Image Sensor	1/2.9" 2.0 Megapixel progressive scan CMOS
Minimum Illumination	0.1LUX/F1.2
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto/Manual
Gain Control(AGC)	Auto/Manual
Lens	3.6mm
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480)
Frame Rate	HD 25/30 fps, Full HD 30 fps
Snapshot	Fastest 1fps JPEG capture
Interface	RJ-45 (10/100Base-T)
Protocol	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, , Alarm Server
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari
Micro SD	Max 32GB, local storage
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V, PoE
Power Consumption	Max 4 W
Weatherproof Standard	IP66
Regulatory	CE, FCC and RoHS
Dimension	φ110mm x 54mm
Weight	400g