


## DS-8104/8108AHF(L)I-ST ATM DVR



## **Key Features**

- H.264 video compression
- 4CIF resolution real time recording
- Dual-stream
- 4 SATA interfaces
- HDD group management



Rear Panel of DS-8108AHF(L)I-ST



- 1. Video in
- 2. Audio in
- 3. Video out, audio out, line in
- 4. RS-232 interface
- 5. VGA
- 6. LAN interface
- 7. eSATA interface
- 8. RS-485 interface 9. Alarm in, alarm out
- 10. 12 VDC power output for camera
- 11. Power switch
- 12. GND

## Specifications

Specifications			
	DS-8104AHF(L)I-ST	DS-8108AHF(L)I-ST	
Video/Audio input			
Analog video input	4-ch 8-ch BNC connector (1.0 Vp-p, 75 Ω); PAL/NTSC self-adaptive		
Audio input	4-ch BNC connector (2.0 Vp-p, 1 kΩ)	8-ch	
Voice talk input	1-ch, BNC connector (2.0 Vp-p, 1 kΩ)		
Video/Audio output			
CVBS output	1-ch, BNC connector (1.0 Vp-p, 75 Ω); Resolution: PAL: 704×576, NTSC: 704×480		
VGA output	1-ch, resolution: 1280×1024 / 60 Hz , 1024×768 / 60 Hz		
LCD Display	Available on DS-8104AHFLI-ST and DS-8108AHFLI-ST models		
Audio output	1-ch, BNC connector (linear, 600 $\Omega$ )	1-ch, BNC connector (linear, 600 $\Omega$ )	
Video/Audio encoding			
Video compression	H.264		
Recording resolution	4CIF/ DCIF / 2CIF / CIF / QCIF		
Frame rate	25 fps(P) /30 fps(N)		
Video bit rate	32 Kbps~2048 Kbps, or user defined (max. 3072 Kbps)		
Stream type	Video, Video & Audio		
Dual stream	Support		
Audio compression	OggVorbis		
Audio bit rate	16kbps		
Synchronous playback	2-ch	4-ch	
Hard disk			
SATA	4 SATA interfaces	4 SATA interfaces	
eSATA	1 eSATA interface (optional)		
Capacity	Up to 2TB capacity for each disk		
External interface			
Network interface	1, RJ45 10M/100M/1000M self-adaptive ethernet interface		
Serial interface	1 RS-485 interface, 1 RS-232 interface		
USB interface	2, USB2.0		
Alarm in	9		
Alarm out	4	4	
General			
Power supply	100 ~ 240 VAC, 6.3A, 50~60 Hz		
Consumption	≤40W (without hard disk or DVD-R/	W) ≤45W (without hard disk or DVD-R/W)	
Working temperature	-10 °C ~+55 °C		
Working humidity	10%~90%	10%~90%	
Chassis	Chassis for ATM DVR	Chassis for ATM DVR	
Dimensions (W × D × H)	180 × 280 × 180 mm	180 × 280 × 180 mm	
Weight	≤5kg (without hard disk or DVD-R/V	≤5kg (without hard disk or DVD-R/W)	