


DS-8104HMI-A Mobile DVR



Key Features

- H.264 video compression
- Up to 4CIF resolution recording
- 2x2.5-inch SATA interfaces
- Patented hard disk vibration-proof and bracing technology
- Built-in 3G (WCDMA/cdma2000) module (optional)
- Built-in GPS module



Rear Panel of DS-8104HMI-A



- | | |
|--|-----------------------------------|
| 1. DC in power input & key startup control interface | 6. GPS antenna interface |
| 2. Aviation plug for video/audio input, power output | 7. USB interface |
| 3. Video / audio output | 8. LAN network interface |
| 4. Main / Aux antenna interface for wireless network | 9. DC out power output (+5V/+12V) |
| 5. SIM / UIM card interface | 10. RS485 interface |
| | 11. Wired-remote control |
| | 12. Alarm input |
| | 13. Alarm output |

Specifications

| | DS-8104HMI-A |
|---------------------------|--|
| Video/Audio input | |
| Video compression | H.264 |
| Video input | 4-ch, aviation interface (PAL / NTSC self-adaptive; 1.0 Vp-p, 75 Ω) |
| Audio compression | OggVorbis, 16Kbps |
| Audio input | 4-ch, aviation interface (linear level, 1 kΩ) |
| Video/Audio output | |
| Preview resolution | PAL:704×576, NTSC:704×480 |
| Encoding resolution | 4CIF/ DCIF / 2CIF / CIF / QCIF |
| Video output | 1-ch, aviation interface (PAL / NTSC self-adaptive; 1.0 Vp-p, 75 Ω) |
| Frame rate | 4CIF:6fps DCIF:12fps 2CIF:15fps CIF/QCIF:25fps (P) /30fps (N) |
| Video bit rate | 32 Kbps~2048 Kbps, or user defined (max. 8 Mbps) |
| Audio output | 1-ch, aviation interface (linear level, 600 Ω) |
| Stream type | Video, Video & Audio |
| Hard disk | |
| SATA | 2 SATA interfaces |
| Size | 2.5-inch |
| External interface | |
| Network interface | 1, RJ45 10M / 100M self-adaptive ethernet interface |
| 3G antenna interface | 2 antennas, SMA interface |
| Serial interface | 1, RS-485 interface |
| USB interface | 1, USB 2.0 |
| Alarm in | 7-ch input, the 8th channel is reserved |
| Alarm out | 2-ch |
| Remote control | IR remote controller |
| GPS | Built-in GPS module, 1 antenna, SMA interface |
| General | |
| Power input | 6-36 VDC |
| Power output | 12V/2A DC, 5V/2A DC output, built-in resettable fuse |
| Power-off delay | Shut down delay after ignition off (from 5mintes to 6hours) |
| Schedule On/Off: | Daily scheduled power on/off (00:00~24:00) |
| Consumption | ≤10W (without SD cards) |
| Working temperature | -15 °C ~ +55 °C |
| Working humidity | 10%~95% |
| Dimensions (W × D × H) | 210 × 236 × 73 mm |
| Weight | ≤3kg (without SD cards) |