

# Value line 3 Megapixel Network Camera



## 3 Megapixel Full HD Network Camera

# SNB-7001

This cost effective 3MP High Definition network camera is a great fit for applications which require high resolution video. The SNB-7001 features contrast enhancement and day/night capabilities for challenging lighting conditions, and is equipped with high-end functionalities such as Tampering Detection and Motion Detection.

- Maximum 3 MP resolution (2048 X 1536)
- Multiple Streaming
- H.264 & MJPEG dual codec
- Tampering Alarm, Motion Detection
- Privacy Masking, Smart codec(ROI encoding)
- Day & Night (Software)

# 3 Megapixel Full HD Network Camera

# SNB-7001




## Specifications

	SNB-7001N/P	
<b>VIDEO</b>		
Imaging Device	1/2.8" 3M PS CMOS	
Total Pixels	2,144(H) X 1,588(V)	
Effective Pixels	2,096(H) X 1,561(V)	
Scanning System	Progressive	
Min. Illumination	Color/ B/W : 0.4 Lux (F1.2, 50IRE)	
Video Out	CVBS : 1.0 Vp-p / 75Ω composite, 704x480(N), 704x576(P), for installation	
<b>HORIZONTAL RESOLUTION</b>		
Lens Type	Manual / DC Auto Iris	
Mount Type	C/CS	
<b>OPERATIONAL</b>		
Camera Title	Off / On (Displayed up to 15 characters)	
Day & Night	(SW) Auto / Color / B/W	
Backlight Compensation	Off / BLC	
Digital Noise Reduction	SSNR (Off / On)	
Motion Detection	Off / On (4 programmable zones, 2Mega 20fps, 3Mega 15fps)	
Privacy Masking	Off / On (12 rectangular zones)	
Sens-up (Frame Integration)	Off / Auto (2x ~ 60x)	
Gain Control	Off / Low / Middle / High	
White Balance	ATW / AWC / Manual / Indoor / Outdoor	
Electronic Shutter Speed	Auto / A.FLK / Manual (1/30 ~ 12,000sec)	
Flip / Mirror	Off / On	
Intelligent Video Analytics	Tampering (3M 15fps, 2M 20fps, 3M 15fps)	
Alarm I/O	Input 1ea	
<b>NETWORK</b>		
Ethernet	RJ-45 (10/100BASE-T)	
Video Compression Format	H.264, MJPEG	
Resolution	<3M Mode> 2048x1536, 1920x1080P(Full HD), 1600x1200, 1280x1024, 1280x960, 1280x720P(HD), 1024x768 800x600, 800x450, 640x480, 640x360, 320x240, 320x180	
	<2M Mode> 1920x1080P(Full HD), 1280x1024, 1280x960, 1280x720P(HD), 1024x768, 800x600, 800x450, 640x480 640x360, 320x240, 320x180	
	<3M Mode> H.264 : Max 20fps at all resolutions MJPEG : 800x600 ~ 320x180 - 20 fps / 1280x1024 ~ 1920x1080 - 15 fps / 2048x1536 - 10 fps	
Max. Framerate	<2M Mode> H.264 : Max 30fps at all resolutions (When WDR ON, Max. framerate is Max 15fps.) MJPEG : 800x600 ~ 320x180 - 30 fps / 1280x1024 ~ 1920x1080 : 15 fps	
	Smart Codec	Yes (Area Based Method)
	Video Quality Adjustment	H.264 : Compression Level, Target Bitrate Level Control / MJPEG : Quality Level Control
Bitrate Control Method	H.264 : CBR or VBR / MJPEG : VBR	
Streaming Capability	Multiple Streaming (Up to 5 Profiles)	
IP	IPv4, IPv6	
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NT, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP	
QoS	IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, ONVIF	
Security	On/Off	
Streaming Method	HTTP(S) Login Authentication / Digest Login Authentication / IP Address Filtering	
Max. User Access	User access Log / 802.1X Authentication	
ONVIF Conformance	Unicast / Multicast	
WEBPAGE LANGUAGE	10 users at Unicast Mode	
Web Viewer	Yes	
	Supported OS : Windows XP / VISTA / 7, MAC OS 10.7 or higher Supported Browser : Internet Explorer 7.0 or Higher, Firefox 9 or higher, Google Chrome 15 or higher, Apple Safari 5.1 or higher	
Central Management Software	NET-i viewer	
<b>ENVIRONMENTAL</b>		
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH	
Storage Temperature / Humidity	-30°C ~ +60°C / Less than 90%RH	
<b>ELECTRICAL</b>		
Input Voltage	12V DC, PoE(IEEE802.3af)	
Power Consumption	Max 3.7W (DC 12V), Max 4.3W (PoE)	
<b>MECHANICAL</b>		
Color / Material	Black, Silver / Aluminium, Plastic	
Dimension (WxHxD)	74.3 x 55.3 x 114.3mm (2.93" x 2.18" x 4.50")	
Weight	170g (0.37 lb)	

## Dimensions

Unit : mm (inch)



## Available Lenses/ Accessories(Optional)



Design and specifications are subject to change without notice.



SAMSUNG TECHWIN AMERICA Inc.  
100 Challenger Rd, Suite 700 Ridgefield Park, NJ 07660  
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920  
Fax : +1-201-373-0124  
www.samsungcctvusa.com



The Eco mark represents Samsung Technwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

■ DISTRIBUTED BY



www.asi.ind.in