

Weatherproof Pass-Through Reader

Weatherproof Pass-Through Magnetic Stripe Card Reader • WP644

- ▶ Pass-through card reading for quickest use
- ▶ Connects to access systems using either Wiegand or Clock-and-Data input
- ▶ Reads security badges, time and attendance badges, parking cards, and more (must be format compatible)
- ▶ Read head assembly is field-adjustable to track location 1 or 2
- ▶ Mounts on single-gang electrical box or directly on a door mullion



ACCESS affordability.

The Dorado WP644 Weatherproof Pass-Through Reader accepts your magnetic stripe ID badge for access control and more!

Offering a wide selection of readers, cards, and card encoders, Dorado represents the access control industry's preferred choice for magnetic stripe readers and cards.

Most access control systems use some form of plastic ID card. With the popular WP644 Pass-Through Reader, one simple motion through the card slot reads a card. A bi-color LED confirms that a card has been read, then changes color when the door unlocks. Use one card for single or multiple purposes!

The Model WP644 Weatherproof Pass-Through Reader combines ease-of-use with installation flexibility. Available with a white or black housing, the Model WP644 reader mounts on a door mullion, directly on the wall, or on a single-gang electrical box. Connect to access control systems using either a Wiegand or Clock-and-Data input.

Magnetic stripe cards are cost-effective, easy to carry, and easy to use. Users have a choice of badge size and artwork, providing a range from simple, single-purpose access cards to customized photo ID badges. The same magnetic stripe card can be double-encoded for applications ranging from door access, time and attendance, and parking to cafeteria meal purchases, vending, and book check-outs. Card encoding (including photo ID fabrication) can be done at HID or at the dealer's facility. Alternatively, the end-user may choose to do their own card encoding using the Model 420 or Model 450 encoder. Choose the card encoding method that meets your needs!

When your application requires magnetic stripe readers and cards, choose the trusted brand.

Specifications

Data Tracks	Track 1 or 2; high or low coercivity								
Card Size	2.125"H x 3.375"L x 0.03" +/- .003" thick (54mm H x 86mm L x .76mm +/- .07mm thick)								
Card Speed	8 to 50 inches (203 to 1270mm) per second								
Data Rate	1 ms per bit								
Approvals	UL 294; FCC Part 15, CE								
Outline w/ Adapter Plate	6.00" x 1.75" x 1.49"; 152 x 38 x 43 mm 7.00" x 2.75" x 1.69"; 178 x 70 x 43 mm								
Connections	Pigtail or Plug-in Connector								
Cable	200' (60m) on five #22 unshielded wires 500' (150m) on five #18 unshielded wires								
Output Formats	Wiegand 26-bit, Wiegand 34-bit, all bits Wiegand, and Clock-and-Data								
Card Format	EMPI, ABA/ISO								
Power	4.75 to 5.25 VDC @ 35mA								
Mounting	Single-gang electrical box, door mullion, or directly on vertical surface								
Lifetime	250,000 wear cycles. MTBF 22,000 hours								
Error Rate	5% false reject 2x10 ⁻⁶ false accept								
Static Discharge	Withstands 20,000 volts								
LED	Red, Green								
Material	GE Lexan (polycarbonate) in white or black								
Temperature	-31° to 150° F (-35° to 66° C) operating								
Humidity	5 to 95%, noncondensing								
Environment	Indoor or outdoor								
Card Format	<table><tr><td>EMPI</td><td>Output Format</td></tr><tr><td>10 Digit ANSI/ISO*</td><td>26 or 34-bit Wiegand</td></tr><tr><td>ABA/ANSI/ISO</td><td>26 or 34-bit Wiegand</td></tr><tr><td></td><td>All bits Wiegand or Clock-and-Data up to 37 characters</td></tr></table>	EMPI	Output Format	10 Digit ANSI/ISO*	26 or 34-bit Wiegand	ABA/ANSI/ISO	26 or 34-bit Wiegand		All bits Wiegand or Clock-and-Data up to 37 characters
EMPI	Output Format								
10 Digit ANSI/ISO*	26 or 34-bit Wiegand								
ABA/ANSI/ISO	26 or 34-bit Wiegand								
	All bits Wiegand or Clock-and-Data up to 37 characters								

* First five digits are site code, last five are card number

Product Compatibility

The Dorado WP644 reader is compatible with mainstream access controllers that accept a Wiegand or Clock-and-Data input from a card reader. The reader accepts cards encoded on track 1 or 2, and are encoded with either ABA/ANSI/ISO or EMPI encoding. EMPI is HID's own encoding format that provides a higher level of security than standard ABA/ANSI/ISO encoding. ABA/ANSI/ISO encoding format refers to the industry standard 75 BPI, 5 bits per character encoding (ISO 7810 Track 2).

Warranty

27-month limited warranty covering parts and labor. (Magnetic stripe reader heads are not covered under this warranty; for complete details, please see HID's Sales Policy.)

How to Order

Dorado WP644W

Weatherproof Pass-Through Magnetic Stripe Card Reader
Color: White
Part Number: 3110-6444

Dorado WP644B

Weatherproof Pass-Through Magnetic Stripe Card Reader
Color: Black
Part Number: 3110-6445

For complete ordering details, please see HID's How to Order Guide found at http://www.hidglobal.com/documents/wiegand_magstripe_htog_en.pdf

© 2009 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2009

MKT-MAG644_DS_EN



ACCESS experience.

<http://www.asi.ind.in>

**Corporate
North America**
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Tel: 1 800 237 7769
Tel: +1 949 732 2000
Fax: +1 949 732 2360

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Tel: +852 3160 9800
Fax: +852 3160 4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Haverhill Business Park
Phoenix Road
Haverhill, Suffolk
CB9 7AE
England
Tel: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840